

SKINNER SERVICE SADDLE CLAMP

SS 6" - 12" MODEL "SS"

BODY DUCTILE IRON CASTINGS ASTM 395-80 536-94
 GASKET BUNA N MATERIAL ASTM D2000 / SAE J200
 DUROMETER 50 +/- 5
 HARDWARE SAE GRADE 5, ZINC PLATED C-1541 STEEL
 E COATING JDM F11T3 18 MILL THICKNESS



Single Hinge Style

Pipe Size (inches)	Outlet Size	Part Number	Approx. Weight (lbs.)	Pipe Size (inches)	Outlet Size	Part Number	Approx. Weight (lbs.)
6	x 3/4	089735	13.5	10	x 3/4	089694	25.5
	1	089733	13.5		1	089693	25.5
	1 1/4	089731	14.25		1 1/4	089692	28.5
	1 1/2	089729	13		1 1/2	088023	28.5
	2	089728	13		2	089691	28.5
6 CI	3/4	089725	15.5	10 CI	x 3/4	089830	25.5
	1	089721	15.5		1	089690	25.5
	1 1/4	089718	15.5		1 1/4	089689	31.5
	1 1/2	089716	15.5		1 1/2	088024	31.5
	2	089714	15.5		2	089686	31.5
8	x 3/4	089710	23.25	12	x 3/4	089682	29
	1	089709	23.25		1	089681	29
	1 1/4	089708	23.25		1 1/4	089837	29
	1 1/2	089707	31.5		1 1/2	088025	29
	2	089706	31.5		2	089679	29
8 CI	x 3/4	089705	24.5	12 CI	x 3/4	089833	29
	1	089703	24.5		1	089676	29
	1 1/4	089701	24.5		1 1/4	089675	29
	1 1/2	089700	24		1 1/2	089674	29
	2	089698	24		2	089673	29

Size (inches)	Torque	Working Pressure	Size (inches)	Torque	Working Pressure
1 1/4	50 ft.lbs.	500 psi	6 x 3/4 to 6 x 1 1/4	60 ft.lbs.	200 psi
1 1/2	50 ft.lbs.	500 psi	6 x 1 1/2 & 6 x 2	60 ft.lbs.	200 psi
2 x 1/2 to 2 x 1 1/4	60 ft.lbs.	500 psi	8 x 3/4 to 8 x 1 1/4	150 ft.lbs.	200 psi
2 x 1 1/2	60 ft.lbs.	200 psi	8 x 1 1/2 & 8 x 2	150 ft.lbs.	250 psi
2 1/2	60 ft.lbs.	200 psi	10 x 3/4 to 10 x 2	150 ft.lbs.	250 psi
3 x 3/4 & 3 x 1	60 ft.lbs.	200 psi	12 x 3/4 to 12 x 2	150 ft.lbs.	200 psi
3 x 1 1/4 & 3 x 2	60 ft.lbs.	250 psi			
4 x 3/4 to 4 x 1 1/4	60 ft.lbs.	300 psi			
4 x 1 1/2 & 4 x 2	60 ft.lbs.	200 psi			